

Rubiomonocoat OIL PLUS 2C

PROTECTS AND COLOURS YOUR WOOD IN ONE SINGLE LAYER.

DESCRIPTION:

Rubio Monocoat Oil Plus 2C is a product of the newest generation which colours your wood and protects it in one layer. The combination of the oil (A) and the accelerator (B) guarantee a quick drying. Can also be applied as renovation and maintenance oil on surfaces which are oiled with RMC.

SPECIFIC FEATURES:

- Molecular bonding with the wood: durable protection!
- 100 % VOC-FREE!
- Respects the natural 'look and feel' of the wood
- Low consumption - 1 liter for 30 to 50 m²
- No starting marks or overlaps
- Easy to maintain
- Doesn't contain water
- Applies to all kinds of wood, on furniture and floors (solid wood, veneer wood, MDF, etc...)
- Durable protection, highly resistant to wear
- Water-resistant: (suited for application in kitchens, bathrooms)
- Resistant to heat until 100 °C
- Fast curing.

DIRECTIONS FOR USE:

1. Untreated wood: sand using the rules of the art. Vacuum thoroughly, eliminate remains of dust with RMC Cleaner.
2. Carefully mix the two components (1 to 2 min) with a ratio of appr. 3 units A to 1 unit B.
3. Once the cleaned surface is dry, spread out a small quantity of RMC Oil Plus 2C (cloth or scrubbing machine with thin beige pad). Work in zones of 5 -10 m².
4. Let absorb during a few minutes. Thoroughly remove all excess of oil (cloth or scrubbing machine with white pad) within 15 minutes per zone. The surface should feel dry! Finish all zones the same way.
5. After 24 - 36 hours the surface can be used .

After 7 days a treatment with water and RMC-products can be applied.

In order to guarantee a long lifespan and protection, the use of Rubio Monocoat maintenance products is imperative.

PROVIDED BY:



Consult the safety sheet before use.

Date TDS: 14/02/11



MADE IN BELGIUM by N.V. MUYLLE - FACON S.A.

Ambachtenstraat 58 - B-8870 Izegem (Industriezone Abele)

Tel. +32 (0)51 30 80 54 - Fax + 32 (0)51 30 99 78 - HRK 1823

info@muylllefacon.be - www.rubiomonocoat.com

CONSUMPTION:

30-50 m²/l, depending on the wood type, sanding and application method.

These usages are merely indicative. Results depend on wood type and method of preparation. It is always recommended to make a sample in order to calculate the exact usage.

INDUSTRIAL APPLICATIONS:

For the application of oxidative and UV drying: see the technical card. The equipment used can be cleaned with **RMC Biocleaner**.

TECHNICAL CHARACTERISTICS:

RMC Oil Plus 2C

Physical state at 20 °C: liquid

Odour: natural oil

Colour: transparent

RMC Accelerator (B)

Physical state: liquid

Colour: colourless to pale yellow

Odour: none

Flash point: >160°C (closed cup)

PACKAGING:

Combined can of 1,3 l: 1 l RMC Oil Plus and 0,3 l RMC Accelerator.

Combined can of 3,5 l: 2,750 l RMC Oil Plus and 0,750 l RMC Accelerator.

STORAGE:

The product can be stored up to 12 months in dry conditions and in its original packaging.

The product may NOT be diluted!

Cloths, saturated with oil, may spontaneously combust. After usage, they need to be soaked in water before disposal.

DISCLAIMER: It is the responsibility of the user to determine through own testing whether the product is suited for its chosen application. MUYLLE FACON NV is not liable for any resultant damage. The above information may be subject to amendments, which will be published in revised versions of the technical sheet. We waive all responsibility for unsatisfactory results that are due to causes unrelated to the quality of the product. This technical information has been collected on the basis of current information and knowledge. The most recent technical sheets can be requested or are available on the website.

