

Alterior Matt

eicó Alterior Matt is a high quality waterborne paint, made of 100% pure Acrylics. It dries to a non-yellowing flat finish and has excellent colour retention. It has low dirt pick-up, good weathering properties and washability. Alterior Matt adheres well to aged alkyd paints, is easy to use and has a very good hiding power. It is an environmentally friendly product with very little odour, APEO and solvent free with low VOC rating (VOC \leq 0.5%). EU limit for this product (Cat A/e): 75g/ltr (2007)/30g/ltr (2010). This product contains max 5g/litre VOC measured at 250°C.

AREA OF USE

Interior and exterior: Walls, ceilings, roof tiles and primed structural steel. Substrates: concrete, masonry, cements, rendering plaster, plaster board, lining paper, glass fibre, woodwork (primed), etc.

APPLICATION

The surface should be stable, firm, dry and free of dust, sand, loose old paint, laitance, dirt, grease and oil. On rough surfaces it may be necessary to dilute the paint by about 10% with fresh water. Use only where application and drying can proceed at temperatures above 5°C, preferably above 10°C and relative humidity below 85%. Temperature of surface should be 5 to 35°C.

TECHNICAL INFORMATION

Gloss level: 5 (Flat matt) Coverage: 8-10m²/litre Volume solid: 38% Solvent/Cleaning of tools: water Drying time: 2-3 touch dry Recoating time: Min. 8-10 hours (depending upon temperature and relative humidity)

SAFETY

Handle with care. Consult Material Safety Data Sheets and follow all local or national regulations. Avoid inhalation, avoid contact with skin and eyes, and do not swallow. Take precautions against

possible risks of fire or explosion, as well as protection of the environment. Apply only in well-ventilated areas. Do not paint if the surface is colder than +5°C. Once opened, keep cans tightly sealed. Wipe away as much paint as possible from painting tools before cleaning with water. Liquid paint waste must not be poured down the drain – dispose it according to local regulations. Hand in empty cans to local authority for recycling. KEEP AWAY FROM CHILDREN

ENVIRONMENTAL PROTECTION

The product is not classified as dangerous for the environment. The product should not be allowed to enter drains or water courses. Dispose in accordance with regulations from local authorities.