

SMOOTH MASONRY PAINT EXTRA-FLEX

Description: A high performance, water thinnable microporous masonry coating, designed for exterior application affording excellent flexibility and weather resistance.

Uses: Suitable for application to roughcast, sand/cement rendering, brickwork and most other masonry surfaces. NOT SUITABLE FOR STOCK BRICKWORK.

Preparation: Treat mould, mildew etc. with Fungicidal Wash Remove all loose, flaky or powdery residues. Porous surfaces should be treated with Stabilising Solution, allowing at least 12 hours drying before coating. Common fletton bricks must be dry, and should be treated as porous.

Application: Stir thoroughly and check colour before use. Apply by brush, roller or spray. Two coats are recommended for optimum durability. Ensure adequate ventilation during application and drying.

Coverage: Approximately 10 sq. metres/litre on smooth surfaces. Rough surfaces will considerably reduce spreading rate.

Drying: Normally 2 hours @ 18° Centigrade and 65% humidity. Recoatable after 4 hours. DO NOT APPLY BELOW 5° CENTIGRADE OR WHEN RAINING OR FOGGY.

Flash Point: Not applicable.

Clean up: Warm soapy water.

Pack sizes: 5 litre

Storage: Keep out of reach of children. Protect from frost.

Colour Range: See colour card. Other colours made on request.